
**Information technology — Coding of
audio-visual objects —**

Part 4:

Conformance testing

**AMENDMENT 2: MPEG-4 conformance
extensions for XMT and media nodes**

Technologies de l'information — Codage des objets audiovisuels —

Partie 4: Essai de conformité

*AMENDMENT 2: Extensions de conformité pour XMT et nœuds
médias*

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

© ISO/IEC 2005

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 2 to ISO/IEC 14496-4:2004 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

Information technology — Coding of audio-visual objects —

Part 4: Conformance testing

AMENDMENT 2: MPEG-4 conformance extensions for XMT and media nodes

Add the following text at the end of Clause 4.

4.9 Extensible MPEG-4 Textual Format (XMT)

4.9.1 Conformance Points

XMT-A conformance points are:

- The XMT language: XMT-A ,
- SDSM and ODSM in mp4 produced from the XMT-A to mp4.

XMT-O conformance points are:

- The XMT language : XMT-O,
- SDSM and ODSM in mp4 produced from the XMT-O to mp4,
- Consumer behavior.

4.9.2 Measurement Procedure

XMT-A conformance can be measured by the following procedure:

1. Conformance on the format :
 - Validate the syntax by the XML Schema parser against the XMT-A Schema
 - Encode the format with a conforming encoder to mp4 and check its conformance.
2. Conformance on encoders: (A conforming encoder, respecting encoding hints, can produce a deterministically coded binary stream for streams defined in MPEG-4 systems).
 - Maintain a set of test cases and their corresponding bit streams (mp4 files) generated by the conforming encoder.
 - Test encoder generates mp4 files from the test cases.
 - Run smart diff tool in mp4 space against mp4 files pair-wise. SDSM and ODSM in mp4 are conformance points. Note: it's not necessarily the same mp4 file.

XMT-O conformance can be verified by the following procedure:

1. Conformance on the format:
 - Validate the syntax by the XML Schema parser against the XMT-A Schema
 - Encode the format with a conforming encoder to mp4 and check its conformance.
2. Conformance on encoders: (consumer behavior is verified).
 - Maintain a set of test cases and their corresponding bit streams (mp4 files) generated by the conforming encoder.
 - Test encoder generates mp4 files from the test cases.
 - Play mp4 files pair-wise by the conforming player and check visual differences.
 - there should be no frame difference ideally
 - there should be no visual difference practically

4.10 MediaSensor

4.10.1 Bitstream conformance

4.10.1.1 Conformance Requirements

BIFS streams shall comply with the specifications in Clause 9 of ISO/IEC 14496-1:2001.

4.10.1.2 Measurement procedure

Syntax of the BIFS stream shall meet the requirements of Clause 9 of ISO/IEC 14496-1:2001.

4.10.1.3 Tolerance

There is no tolerance for bitstream syntax checking. The diagnosis is pass or fail.

4.10.2 Terminal conformance

4.10.2.1 Conformance Points

MediaSensor conformance points are defined in the **MediaSensor** node by its fields. The **mediaCurrentTime**, **streamObjectStartTime**, **mediaDuration**, and **info** fields may not contain any valid information if the media time of the media in the **url** field is not known.

4.10.2.2 Measurement Procedure

The terminal shall produce formatted output each time a media node that references the same stream as a **MediaSensor** node become active. The output is to include:

- The stream object.
- The **mediaCurrentTime**, **streamObjectStartTime**, **mediaDuration**, and **info**. The times are given in seconds.

Further, the terminal shall then output the **mediaCurrentTime** for each AU in the stream object.

4.10.2.3 Output Format

The output format is in XML. An example is:

```
<MediaSensor url="od:4" mediaCurrentTime="0"
              streamObjectStartTime="1021"
              mediaDuration="1200"
              info="MPEG News Segment"/>
<mediaCurrentTime time="0.016"/ >
<mediaCurrentTime time="0.032"/ >
<mediaCurrentTime time="0.048"/ > . . . . .
```

4.10.2.4 Tolerance

The conformance is passed when the time values reflect the correct media Time, as defined in ISO/IEC 14496-1:2001.

4.11 MediaControl

4.11.1 Bitstream conformance

4.11.1.1 Conformance Requirements

BIFS streams shall comply with the specifications in Clause 9 of ISO/IEC 14496-1:2001.

4.11.1.2 Measurement procedure

Syntax of the BIFS stream shall meet the requirements of Clause 9 of ISO/IEC 14496-1:2001.

4.11.1.3 Tolerance

There is no tolerance for bitstream syntax checking. The diagnosis is pass or fail.

4.11.2 Terminal conformance

4.11.2.1 Conformance Points

MediaControl conformance points the following:

- The **mediaStartTime** and **mediaStopTime** of the delivered stream object shall conform to the definition of these fields in the node.
- The **enabled** flag shall be set to true in the last set node and false in all others referring to the same stream.
- The **mute** field shall cause the rendering to stop.

It is important to note that **preRoll** and **mediaSpeed** are 'best effort' mechanisms that do not constitute conformance points.

4.11.2.2 Measurement Procedure

The terminal shall produce formatted output each time a media node that references the same stream as a MediaSensor node become active. The output is to include:

- The stream object.
- The mediaCurrentTime for the stream for each AU in the stream object.
- The state of the enabled field.
- The state of the mute field.

4.11.2.3 Output Format

The output format is in XML. An example is:

```
<mediaCurrentTime time="0.016" enabled=" TRUE" mute=" FALSE"/>  
<mediaCurrentTime time="0.032" enabled=" TRUE" mute=" FALSE"/>  
<mediaCurrentTime time="0.048" enabled=" TRUE" mute=" TRUE"/> . . . . .
```

4.11.2.4 Tolerance

The conformance is passed when the time values reflect the correct media Time, as defined in ISO/IEC 14496-1:2001. The rendering functionality must be observed visually.

4.12 MediaBuffer

4.12.1 Bitstream conformance

4.12.1.1 Conformance Requirements

BIFS streams shall comply with the specifications in Clause 9 of ISO/IEC 14496-1:2001

4.12.1.2 Measurement procedure

Syntax of the BIFS stream shall meet the requirements of Clause 9 of ISO/IEC 14496-1:2001.

4.12.1.3 Tolerance

There is no tolerance for bitstream syntax checking. The diagnosis is pass or fail.

4.12.2 Terminal conformance

4.12.2.1 Conformance Points

MediaBuffer conformance points the following:

- The buffer size used to store incoming media samples.
- The ability to substitute media samples from the buffer rather than from the server, when appropriate.