INTERNATIONAL STANDARDIZED PROFILE

ISO/IEC ISP 12062-5

Third edition 2003-06-15

Information technology —International Standardized Profiles AMH2n — Message Handling Systems —Interpersonal Messaging —

Part 5:

AMH24 — IPM Requirements for Enhanced MS Access (P7)

Technologies de l'information — Profils normalisés internationaux AMH2n — Systèmes de messagerie — Messagerie entre personnes — Partie S. AMH24 — Prescriptions IPM pour accès accru à MS (P7)



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.

STANDARDS SOCOM. Click to remine full rule of ESONEC LEAR NAME OF SOME CHANGE OF

© ISO/IEC 2003

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Contents

		age
Fc	preword	iv
Int	troduction	V
1	Scope	
2	Normative references	2
	Terms and definitions	
	Abbreviations	
5	Conformance	4
Ar	nnexes	
Α	ISPICS Proformator ISO/IEC ISP 12062-5 (AMH24)	6
В	ISPICS Requirements List for ISO/IEC ISP 12062-5 (AMH24)	.15
С	Amendments and corrigenda	.23
Б,	Bibliography	.24

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

In addition to developing International Standards, ISO/IEC JTC 1 also develops International Standardized Profiles. An International Standardized Profile is an internationally agreed, harmonized document which identifies a standard or group of standards, together with options and parameters, necessary to accomplish a function or a set of functions. Draft International Standardized Profiles adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standardized Profile requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC ISP 12062-5 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*.

This third edition cancels and replaces the second edition (ISO/IEC ISP 12062-5:1997), which has been technically revised.

ISO/IEC ISP 12062 consists of the following parts under the general title *Information technology* — *International Standardized Profiles AMH2n* — *Message Handling Systems* — *Interpersonal Messaging*:

- Part 1: IPM MHS Service Support
- Part 2: AMH21 IPM Content
- Part 3: AMH22 IPM Requirements for Message Transfer (P1)
- Part 4: AMH23 and AMH25 IPM Requirements for MTS Access (P3) and MTS 94 Access (P3)
- Part 5: AMH24 PM Requirements for Enhanced MS Access (P7)
- Part 6: AMH26 IPM Requirements for Enhanced MS 94 Access (P7)

Introduction

This part of ISO/IEC ISP 12062 is defined within the context of Functional Standardization, in accordance with the principles specified by ISO/IEC TR 10000, "Framework and Taxonomy of International Standardized Profiles". The context of Functional Standardization is one part of the overall field of Information Technology (IT) standardization activities, covering base standards, profiles, and registration mechanisms. A profile defines a combination of base standards that collectively perform a specific well-defined IT function. Profiles standardize the use of options and other variations in the base standards, and provide a basis for the development of uniform, internationally recognized system tests.

One of the rôles for an ISP is to serve as the basis for the development (by organizations other than ISO and IEC) of internationally recognized tests. ISPs are produced not simply to 'legitimize' a particular choice of base standards and options, but to promote real system interoperability. The development and widespread acceptance of tests based on this and other ISPs is crucial to the successful realization of this goal.

The text for this part of ISO/IEC ISP 12062 was originally developed in close cooperation between the MHS Expert Groups of the three Regional Workshops: the North American OSE Implementors' Workshop (OIW), the European Workshop for Open Systems (EWOS) (jointly with the corresponding expert group of the European Telecommunications Standards Institute - ETSI) and the OSI Asia-Oceania Workshop (AOW). The first and second editions of this part of ISO/IEC ISP 12062 were harmonized between these three Workshops and ratified by the plenary assemblies of all three Workshops.

Responsibility for maintenance and further development of MHS ISPs has been transferred to ISO/IEC JTC1/SC33/WG1, who have produced this edition to encompass additions and corrections to ISO/IEC 10021. Because new core requirements have been added for support of Universal Characters in addresses which will take time to be implemented within MHS systems, it is expected that the second edition of this part of ISO/IEC ISP 12062 will remain available for an overlap period.

STANDARDSISO.COM

Information technology — International Standardized Profiles AMH2n — Message Handling Systems — Interpersonal Messaging —

Part 5:

AMH24 — IPM Requirements for Enhanced MS Access (P7) EC 126 15085;

1 Scope

1.1 General

This part of ISO/IEC ISP 12062 covers access to a message store (MS) in an Interpersonal Messaging (IPM) environment using the P7 MS Access Protocol (see also figure 17) These specifications form part of the Interpersonal Messaging application functions, as defined in the parts of ISO/IEC ISP 12062, and are based on the Common Messaging content type-independent specifications in ISO/IEC ISP 10611.

The type of MS access specified in this part of ISO/IEC ISP 2062 allows an IPM user agent (UA) to interact with an MS in a full and flexible manner without having to retrieve complete messages. Minimal attribute support for MS access in an IPM environment can be specified by claiming conformance to profile AMH13 with an additional claim of support of IPM MS attributes (see subclause A.3.1 of ISO/IEC ISP 10611-5). Annex A of this part of ISO/IEC ISP 12062 may be used in such a case

1.2 Position within the taxonomy

This part of ISO/IEC ISP 12062 is the fifth part of a multipart ISP identified in ISO/IEC TR 10000-2 as "AMH2, Message Handling Systems - Interpersonal Messaging".

This part of ISO/IEC ISP 12062 specifies the following profile:

AMH24 - IPM Requirements for Enhanced MS Access (P7)

The AMH24 profile may be combined with any T-Profiles (see ISO/IEC TR 10000) specifying the OSI connection-mode Transport service.

1.3 Scenario

The model used is one of access to a IPM message store (MS) by an IPM MS-user - specifically, the intercommunication between an IPM MS and an IPM MS-user (i.e. an IPM user agent) using the P7 protocol, as shown in figure 1.

The AMH24 profile covers all aspects of the MS Abstract Service, as defined in the 1990 publication of ISO/IEC 10021-5, when realized using the P7 protocol in an IPM environment. (The AMH26 profile covers the MS 94 Abstract Service).




Figure 1 - AMH24 scenario

The OSI upper layer services and protocols to support the Message Handling Systems functions covered by the AMH24 profile are specified in subclause 1.3 of ISO/IEC ISP 10611-5.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

Amendments and corrigenda to the base standards referenced are listed in annex C.

NOTES

1 - References in the body of this part of ISO/IEC ISP 12062 to specific clauses of ISO/IEC documents shall be considered to refer also to the corresponding clauses of the equivalent ITU-T Recommendations (as noted below) unless otherwise stated.

2 - Informative references are found in annex D.

ISO/IEC TR 10000-1:1998, Information technology - Framework and taxonomy of International Standardized Profiles - Part 1: General principles and documentation framework

ISO/IEC TR 10000-2:1998, Information technology - Framework and taxonomy of International Standardized Profiles - Part 2: Principles and Taxonomy for OSI Profiles

ITU-T Recommendation F.400/X.400 (1999), Message Handling Systems - System and service overview

ISO/IEC 10021-1:2003, Information technology - Message Handling Systems (MHS) - Part 1: System and service overview [see also ITU-T Recommendation F.400/X.400]

ITU-T Recommendation X.402 (1999) | ISO/IEC 10021-2:—¹⁾, Information technology - Message Handling Systems (MHS): Overall architecture

ITU-T Recommendation X.413 (1999) | ISO/IEC 10021-5:1999, Information technology - Message Handling Systems (MHS): Message store: Abstract service definition

ITU- T Recommendation X.419 (1999) | ISO/IEC 10021-6:1996, Information technology - Message Handling Systems (MHS): Protocol specifications

ITU-T Recommendation X.420 (1999) | ISO/IEC 10021-7:—²⁾, Information technology - Message Handling Systems (MHS): Interpersonal Messaging System

ISO/IEC ISP 1061/1-5:2003, Information technology - International Standardized Profiles AMH1n - Message Handling Systems - Common Messaging - Part 5: AMH13 - MS Access (P7)

ISO/IEC ISP 12062-1:2003, Information technology - International Standardized Profiles AMH2n - Message Handling Systems - Interpersonal Messaging - Part 1: IPM MHS Service Support

ISO/IEC ISP 12062-2:2003, Information technology - International Standardized Profiles AMH2n - Message Handling Systems - Interpersonal Messaging - Part 2: AMH21 — IPM Content

¹⁾ To be published. (Revision of ISO/IEC 10021-2:1996)

²⁾ To be published. (Revision of ISO/IEC 10021-7:1997)

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

Terms used in this part of ISO/IEC ISP 12062 are defined in the referenced base standards; in addition, the following terms are defined.

3.1 General

Basic requirement: an Element of Service, protocol element, procedural element or other identifiable feature specified in the base standards which is required to be supported by all MHS implementations.

Functional group: a specification of one or more related Elements of Service, protocol elements, procedural elements or other identifiable features specified in the base standards which together support a significant optional area of MHS functionality.

NOTE - A functional group can cover any combination of MHS features specified in the base standards for which the effect of implementation can be determined at a standardized external interface - i.e. via a standard OSI communications protocol (other forms of exposed interface, such as a standardized programmatic interface, are outside the scope of this version of ISO/IEC ISP 12062).

3.2 Support classification

To specify the support level of operations, arguments, results, attributes and other protocol features for this part of ISO/IEC ISP 12062, the following terminology is defined.

The following classifications are used in this part of ISO/IEC ISP 12062 to specify <u>static</u> conformance requirements - i.e. <u>capability</u>.

In the case of arguments and results (protocol elements), the classification is relative to that of the containing element, if any. Where the constituent elements of a non-primitive element are not individually specified, then each shall be considered to have the classification of that element. Where the range of values to be supported for an element is not specified, then all values defined in the MHS base standards shall be supported.

mandatory support (m): the element or feature shall be fully supported. An implementation shall be able to generate the element, and/or receive the element and perform all associated procedures (i.e. implying the ability to handle both the syntax and the semantics of the element) as relevant, as specified in the MHS base standards. Where support for origination (generation) and reception are not distinguished, then both capabilities shall be assumed. Mandatory support of an MS attribute requires that it is supported in the context of all applicable supported operation arguments and results and also for use within a selector to the level of support claimed for the filter item. The way in which attribute values are stored by an MS implementation, or used by a UA implementation, is otherwise a local matter.

optional support (o): an implementation is not required to support the element or feature. If support is claimed, the element shall be treated as if it were specified as mandatory support. If support is not claimed, and the element is an argument, then an implementation shall generate an appropriate error indication if the element is received. If support is not claimed, and the element is a result, then an implementation may ignore the element if it is received.

4 **Abbreviations**

AMH Application Message Handling

BC **Business Class** CV Conversion DIR Use of Directory DL **Distribution List** FG Functional group

IPM Interpersonal Messaging

ISP International Standardized Profile

LD **Latest Delivery**

MHS Message Handling Systems

MS Message store ΜT Message transfer MTA Message transfer agent Message Transfer System MTS OSI Open Systems Interconnection

PD **Physical Delivery RED** Redirection

RoC Return of Content

SEC Security UA User agent

Support level for protocol elements and features (see 3.2):

mandatory support m optional support 0

5 Conformance

anthe full PDF of Isolitic IsP 12082.5:2003 This part of ISO/IEC ISP 12062 states requirements upon implementations to achieve interworking. A claim of conformance to this part of ISO/IEC ISP 12062 is a claim that all requirements in the relevant base standards are satisfied, and that all requirements in the following clauses and in annexes A and B of this part of ISO/IEC ISP 12062 are satisfied.

Conformance statement 5.1

For each implementation claiming conformance to profile AMH24 as specified in this part of ISO/IEC ISP 12062, a PICS shall be made available stating support or non-support of each option identified in this part of ISO/IEC ISP 12062.

The scope of conformance to profile AMH24 covers both MSs and MS-users (i.e. UAs). A claim of conformance to profile AMH24 shall confirm that the implementation supports profile AMH13 as specified in ISO/IEC ISP 10611-5 and shall state whether the implementation claims conformance as an MS or as an MS-user.

A claim of conformance to profile AMH24 as an MS-user shall confirm that the implementation supports profile AMH21 as specified in ISO/IEC ISP 12062-2.

5.2 MHS conformance

This part of ISO/IEC ISP 12062 specifies implementation options or selections such that conformant implementations will satisfy the conformance requirements of ISO/IEC 10021 and the ITU-T X.400 Recommendations.

Implementations conforming to profile AMH24 as specified in this part of ISO/IEC ISP 12062 shall conform to the basic requirements of profile AMH13, as specified in ISO/IEC ISP 10611-5.

Implementations conforming to profile AMH24 as specified in this part of ISO/IEC ISP 12062 shall additionally implement all the mandatory support (m) features identified as basic requirements in annexes A and B except those features that are components of an unimplemented optional feature. It shall be stated which optional support (o) features are implemented.

For implementations conforming to profile AMH24 as specified in this part of ISO/IEC ISP 12062, it shall be stated whether or not they support any of the optional functional groups as specified in ISO/IEC ISP 12062-1 which are applicable to the scope of this profile and to the role (i.e. MS or MS-user) for which conformance is claimed. For each functional group for which support is claimed, an implementation shall additionally implement all the mandatory support (m) features identified for that functional group in annex B except those features that are components of an unimplemented optional feature. It shall be stated which optional support (o) features are implemented.

Implementations shall support the procedures associated with supported protocol elements as specified in the base standards and as further specified in ISO/IEC ISP 12062-1. The MHS Elements of Service corresponding to such procedures are indicated in annex A of ISO/IEC ISP 12062-1.

5.3 Underlying layers conformance

Implementations conforming to profile AMH24 as specified in this part of ISO/IEC ISP 12062 shall also meet the requirements for support of underlying layers as specified in subclause 5.3 of ISO/IEC ISP 10611-5.

Annex A³

(normative)

ISPICS Proforma

for ISO/IEC ISP 12062-5 (AMH24)

This annex modifies the P7 ISPICS proforma as contained in annex A of ISO/IEC ISP 10611-5 for the purposes of conformance to the AMH24 profile.

NOTE - The tables and other material in this annex replace the corresponding clauses of annex A of ISO/EC ISP 10611-5 or should otherwise be inserted as appropriate.

In the event of a discrepancy becoming apparent in the body of this part of ISO/IEC ISP32062 and the tables in this annex, this annex is to take precedence.

Clause A.1 specifies the basic requirements for conformance to profile AMH24 Clause A.2 specifies additional requirements to those specified in A.1 for each of the optional functional groups if conformance to such a functional group is claimed. Clause A.3 allows additional information to be provided for certain aspects of an implementation where no specific requirements are included in ISO/IEC ISP 12062 or in ISO/IEC ISP 10611. All three clauses shall be completed as appropriate.

In each table, the "Base" column reflects the level of support required for conformance to the base standard and the "Profile" column specifies the level of support required by this ISP (using the classification and notation defined in 3.2).

The "Ref" column is provided for cross-referencing purposes. The notation employed for references also indicates composite elements which contain sub-elements (a sub-element reference is prefixed by the reference of the composite element).

The "Support" column is provided for completion by the supplier of the implementation as follows:

Y the element or feature is fully supported (i.e. satisfying the requirements of the m profile support classification)

N the element or feature is not supported, further qualified to indicate the action taken on receipt of such an element as follows:

ND- the element is discarded/ignored

NR - the PDU is rejected (with an appropriate error indication where applicable)

the element or feature is not applicable (i.e. a major feature or composite protocol element which includes this element or feature is not supported)

Users of this International Standardized Profile may freely reproduce the ISPICS proforma in this annex so that it can be used for its intended purpose and may further publish the completed ISPICS.

³Copyright release for ISPICS proformas

A.0 Identification of the implementation

A.0.1 Identification of PICS

Ref	Question	Response
1	Date of statement (YYYY-MM-DD)	
2	PICS serial number	ကိ
3	System conformance statement cross reference	0.15.700x

A.0.2 Identification of IUT

Ref	Question	Response
1	Implementation name	
2	Implementation version	
3	Hardware name	
4	Hardware version	"by
5	Operating system name	
6	Operating system version	
7	Special configuration	
8	Other information	

A.0.3 Identification of supplier

Ref	Question	Response
1	Organization name	
2 JDA	Contact name(s)	
34	Address	
4	Telephone number	
5	Telex number	
6	Fax number	
7	E-mail address	
8	Other information	

ISO/IEC ISP 12062-5:2003(E)

A.0.4 Identification of protocol

Ref	Question	Response
1	Title, reference number and date of publication of the protocol standard	
2	Protocol version(s)	not applicable
3	Addenda/amendments/corrigenda implemented	
4	Defect reports implemented	not applicable

A.0.5 Type of implementation

Ref	Implementation Type	Response
1	MS-user (UA)	
2	MS (co-located with MTA)	
3	MS (P3 interface to MTA)	of of

NOTE - A separate PICS shall be completed for each implementation type for which conformance is claimed.

A.0.6 Global statement of conformance

Ref	Question	Response
1	Are all mandatory base standards requirements implemented?	

A.0.7 Statement of profile conformance

Ref	Question	Response	Comments
1	Are all mandatory requirements of profile AMH13 implemented?		
2	Are all mandatory requirements of profile AMH24 implemented?		
3 5	Are all mandatory requirements of any of the following optional functional groups implemented?		
3.1	IPM Conversion (CV)		not applicable in the case of an MS
3.2	IPM Distribution List (DL)		only class DL+ER is applicable
3.3	IPM Physical Delivery (PD)		not applicable in the case of an MS
3.4	IPM Redirection (RED)		not applicable in the case of an MS

Ref	Question	Response	Comments
3.5	IPM Latest Delivery (LD)		not applicable in the case of an MS
3.6	IPM Return of Content (RoC)		
3.7	IPM Security (SEC)		class(es):
3.8	IPM Use of Directory (DIR)		class(es):
3.9	IPM Business Class (BC)		(%). (%).

NOTE - The functional group IPM Simple Protected Password (SPP) is not applicable in the 1988 P7 context.

A.1 Basic requirements

A.1.4 MessageSubmissionEnvelope

The following elements are additional to those specified in annex A.1.4 of ISO/IEC ISP 10611-5.

Ref	Element	MS-user MS		Support	Notes/References		
		Base	Profile	Base	Profile		
9.4.15	IPMPerRecipientEnvelopeExtension s	0	S LW	0	m		
9.4.15.1	blind-copy-recipients	No.	0	0	m		
9.4.15.2	body-part-encryption-token	0	0	0	0		
9.4.15.3	forwarded-content-token	0	0	0	0		

A.1.6 AutoForwardRegistration Parameter

The following elements are additional to those specified in annex A.1.6 of ISO/IEC ISP 10611-5.

Ref	Element	MS-user MS		S	Support	Notes/References	
اللم		Base	Profile	Base	Profile		
49	auto-forwarding-comment	0	0	0	m		
4.2	cover-note	0	0	0	m		
4.3	this-ipm-prefix	0	0	0	m		

ISO/IEC ISP 12062-5:2003(E)

A.1.12 IPM-specific attributes

Ref	Attribute	MS-	MS-user MS		Support	Notes/References	
		Base	Profile	Base	Profile		
1	acknowledgement-mode	0	0	0	m		
2	authorization-time	0	0	0	0		<u></u>
3	authorizing-users	0	0	0	m		2003
4	auto-forward-comment	0	0	0	m		1005,25003
5	auto-forwarded	0	0	0	m		1200
6	bilaterally-defined-body-parts	0	0	0	0	SK	
7	blind-copy-recipients	o	o	0	m		
8	body	m	m	m			
9	body-part-encryption-token	0	0	0	o		
10	body-part-security-label	0	0	(S)	0		
11	body-part-signature-verification- status	0	the	0	0		
12	body-part-signatures	0 118	,, ,	0	0		
13	circulation-list-recipients	4	0	0	m		
14	conversion-EITs	0	0	0	m		
15	copy-recipients .	0	0	0	m		
16	discard-reason	0	0	0	m		
17	distribution-codes	0	0	0	0		
18	encrypted-body-parts	0	I	0	i		
19	encrypted-data	0	I	0	-		
20	encrypted-parameters	0	I	0	i		
21	expiry-time	0	0	0	m		
22	extended-body-part-types	0	0	0	m		
23	(extended-body-parts)						see A.1.12.1
24	extended-subject	0	0	0	m		

Ref	Attribute	MS-	user	М	s	Support	Notes/References
		Base	Profile	Base	Profile		
25	forwarded-content-token	0	0	0	0		
26	forwarding-token	0	0	0	0		
27	g3-facsimile-body-parts	0	0	0	0		03
28	g3-facsimile-data	0	0	0	0		67.5003
29	g3-facsimile-parameters	0	0	0	0	C	501
30	g4-class1-body-parts	0	0	0	0	CO	
31	heading	m	m	m	e C	2	
32	ia5-text-body-parts	0	0	0	m		
33	ia5-text-data	0	0	84	0		
34	ia5-text-parameters	0	0	5 °	0		
35	importance	0	Fell	0	m		
36	incomplete-copy	0 👋	Ø 0	0	0		
37	information-category	JIO	0	0	0		
38	ipm-entry-type	m	m	m	m		
39	ipm-preferred-recipient	0	0	0	m		
40	ipm-security-label	0	0	0	0		
41	ipm-synopsis	0	0	0	m		
42	ipn-originator	0	0	0	m		
43	languages	0	0	0	m		
44	manual-handling-instructions	0	0	0	0		
45	message-body-parts	0	0	0	m		
46	message-data	0	0	0	0		
47	message-parameters	0	0	0	0		
48	mixed-mode-body-parts	0	0	0	0		
49	nationally-defined-body-parts	0	0	0	0		
50	non-receipt-reason	0	0	0	m		

ISO/IEC ISP 12062-5:2003(E)

Ref	Attribute	MS-	user	MS		Support	Notes/References
		Base	Profile	Base	Profile		
51	notification-extensions	0	0	0	0		
52	nrn-extensions	0	0	0	0		
53	nrn-requestors	0	0	0	o ¹		Co
54	obsoleted-ipms	0	0	0	m		2003
55	originator	0	0	0	m		5,5,00
56	originators-reference	0	0	0	0		1200
57	other-notification-type-fields	0	0	0	0	S	·
58	precedence	0	0	0	0		
59	precedence-policy-identifier	0	0	0	9		
60	primary-recipients	0	0	0	5 m		
61	receipt-time	0	0	(60)	m		
62	related-ipms	0	0 4	0	m		
63	replied-to-ipm	0	Nill	0	m		
64	reply-recipients	ojik	0	0	m		
65	reply-requestors	**	0	0	o¹		
66	reply-time	0	0	0	m		
67	returned-ipm	0	0	0	0		
68	rn-extensions	0	0	0	0		
69	rn-requestors	0	0	0	o ¹		
70	sensitivity	0	0	0	m		
71	subject	0	0	0	m		
72	subject-ipm	m	m	m	m		
73	suppl-receipt-info	0	0	0	0		
74	teletex-body-parts	0	0	0	0		
75	teletex-data	0	0	0	0		
76	teletex-parameters	0	0	0	0		

Ref	Attribute	MS-	user	MS		Support	Notes/References
		Base	Profile	Base	Profile		
77	this-ipm	m	m	m	m		
78	videotex-body-parts	0	0	0	0		
79	videotex-data	0	0	0	0		<i>6</i> 5
80	videotex-parameters	0	0	0	0		(2). (2).

A new auto-correlation IPM attribute type is defined in the 1996 publication of the base standard, in replacement of this attribute type.

A.1.12.1 Extended body part attribute support

Ref	Extended Body Part Attribute	MS-	user	M	Olle	Support	Notes/References
		Base	Profile	Base	Profile		
1	ia5-text-body-parts	0	0	% o	m		
2	g3-facsimile-body-part	0	4911	0	0		
3	g4-class1-body-part	0 👋	0	0	0		
4	teletex-body-part	jien	0	0	0		
5	videotex-body-part encrypted-body-part	0	0	0	0		
6	encrypted-body-part	0	0	0	0		
7	message-body-parts	0	0	0	m		
8	mixed-mode-body-part	0	0	0	0		
9	bilaterally-defined-body-part	0	0	0	0		
10	nationally-defined-body-part	0	0	0	0		
11 ANI	general-text-body-parts	0	0	0	m		
125	file-transfer-body-part	0	m	0	m		
13	voice-body-part	0	0	0	0		
14	oda-body-part	0	0	0	0		see ISO/IEC 8613-5
15	report-body-part	0	m	0	m		
16	notification-body-part	0	m	0	m		
17	forwarded-content-body-part	0	m ¹	0	m ¹		

Ref	Extended Body Part Attribute	MS-	user	M	s	Support	Notes/References
		Base	Profile	Base	Profile		
18	pkcs7-body-part	0	0	0	0		
4	other (specify)	0	0	0	0		
							2067.25:3003
1 Support for IPM content-types is mandatory, support for other content-types is optional.							
STA	ort for IPM content-types is mandato	*Oile	nineful	ROF	i i solik		

Annex B

(normative)

ISPICS Requirements List

for ISO/IEC ISP 12062-5 (AMH24)

In the event of a discrepancy becoming apparent in the body of this part of ISO/IEC ISP 12062 and the tables in this annex, this annex is to take precedence.

This annex specifies the support constraints and characteristics of ISO/IEC ISP 12062-5 on what shall or may appear in the implementation columns of an ISPICS. Such requirements are additional to those specified in annex A of ISO/IEC ISP 10611-5 as modified by annex A of this part of ISO/IEC ISP 12062 (references are to the corresponding table entries in those annexes).

Clause B.1 specifies the basic requirements for conformance to profile AMH24. Clause B.2 specifies additional requirements to those specified in B.1 for each of the optional functional groups if conformance to such a functional group is claimed.

In each table, the "Profile" column specifies the level of support required by this ISP (using the classification and notation defined in 3.2). The supplier of an implementation for which conformance to profile AMH24 is claimed should complete the Support column of the tables in annex A of ISO/IEC ISP 10611-5 as modified by annex A of this part of ISO/IEC ISP 12062 in accordance with the requirements contained therein together with any additional requirements in this annex for the type of implementation (i.e. MS or MS-user) in question.

The "Ref" column is provided for cross-referencing purposes. The notation employed for references also indicates composite elements which contain sub-elements (a sub-element reference is prefixed by the reference of the composite element).

B.1 Basic requirements

B.1.1 Supported application contexts

No additional requirements.

B.1.2 Supported operations

Ref	Element	Profile	
		MS-user	MS
A.1.2.3/1	Summarize	m	
A.1.2.3/2	List	m	

Ref	Element	Pro	file
		MS-user	MS
A.1.2.3/1	Summarize	m	
A.1.2.3/2	List	m	
	ageSubmissionEnvelope		III PI
B.1.5 Probe	I requirements. SubmissionEnvelope I requirements. orwardRegistrationParan	Pro MS-user m	
B.1.5 Probe No additiona B.1.6 AutoF	SubmissionEnvelope I requirements.	neter to view the h	
B.1.5 Probe	SubmissionEnvelope I requirements. orwardRegistrationParan	iiC'	

B.1.7 AutoAlertRegistrationParameter

No additional requirements.

B.1.8 Common data types

No additional requirements.

B.1.9 Extension data types

No additional requirements.

B.1.10 **OR-names**

Ref	OR-Name Form	Pro	file
		MS-user	MS
A.1.10.1/2	numeric OR-address	m	
A.1.10.1/3	terminal OR-address	m	

General attributes B.1.11

A.1.10.1/2	numeric OR-address	m	
A.1.10.1/3	terminal OR-address	m	
B.1.11 Ge	eneral attributes		ofile MS
Ref	Attribute	Pro	ofile
		MS-user	MS
A.1.11/5	content-correlator		m
A.1.11/6	content-identifier		m S
A.1.11/9	content-returned		¢ €
A.1.11/11	conversion-with-loss-prohibited	"bl	m
A.1.11/12	converted-EITs	Sin	m
A.1.11/15	delivery-flags		m
A.1.11/17	dl-expansion-history		m
A.1.11/29	originally-intended-recipient-name		m
A.1.11/22	message- identifier		m
A.1.11/21	message-delivery-time		m
A.1.11/25	message-submission-time		m
A.1.11/28	original-EITs		m
A.1.11/32	other-recipient-names		m
A.1.11/38	redirection-history		m
A.1.11/41	reporting-DL-name		m
A.1.11/48	this-recipient-name		m

B.2 Optional functional groups

The following requirements are <u>additional</u> to those specified in B.1 if support of the functional group is claimed.

B.2.1 IPM Conversion (CV)

B.2.1.1 MessageSubmissionEnvelope

Ref	Element	Pro	file
		MS-user	MS
A.1.4/8.3	conversion-with-loss-prohibited	m	
A.1.4/9.3	explicit-conversion	m	

B.2.1.2 ProbeSubmissionEnvelope

Ref	Element	Pro	file
		MS-user	MS
A.1.5/7.3	conversion-with-loss-prohibited	m	160
A.1.5/8.3	explicit-conversion	m	FUI!

B.2.2 IPM Distribution List

There are no additional requirements to those specified for the Common Messaging DL FG in annex A.2.1 of ISO/IEC ISP 10611-5.

B.2.3 IPM Physical Delivery (PD)

The following requirements are additional to those specified for the Common Messaging PD FG in annex A.2.2 of ISO/IEC ISP 10611-5.

B.2.3.1 MessageSubmissionEnvelope

Ref	Element	Profile	
TAME		MS-user	MS
A.1.4/8.5	originator-return-address	m	

B.2.4 IPM Redirection (RED)

B.2.4.1 MessageSubmissionEnvelope

Ref	Element	Profile	
		MS-user	MS
A.1.4/9.4.1	originator-requested-alternate- recipient	m	

B.2.4.2 ProbeSubmissionEnvelope

Ref	Element	Pro	file	
		MS-user	MS	0
A.1.4/9.4.1	originator-requested-alternate- recipient	m		2062.5:2003
B.2.4.2 Probe	SubmissionEnvelope			12062
Ref	Element	Profile		SP
		MS-user	MS	IKC 13
A.1.5/8.4.1	originator-requested-alternate- recipient	m	9	(50)
B.2.4.3 Comr	non data types		80K	,
		(2)]

B.2.4.3 Common data types

Ref	Element	Profile	
	3	MS-user	MS
A.1.8/5.3	alternate-recipient-allowed	m	

B.2.5 IPM Latest Delivery (LD)

There are no additional requirements to those specified for the Common Messaging LD FG in annex A.2.3 of ISO/IEC ISP 10611-5.

B.2.6 IPM Return of Content (RoC)

There are no additional requirements to those specified for the Common Messaging RoC FG in annex A.2.4 of ISO/IEC ISP 10611-5.

B.2.7 IPM Security (SEC)

There following requirements are additional to those specified for the Common Messaging SEC FG in annex A.2.5 of ISO/IEC ISP 10611-5.

Requirements are as specified in annex A.2.2 of ISO/IEC ISP 12062-2, plus the following requirements.