

SAE WEB ADDRESS: <http://www.sae.org>

TABLE 1

PART NUMBER	L	G MIN	K MAX	APPROX MASS LB/100	PART NUMBER	L	G MIN	K MAX	APPROX MASS LB/100
AS3162-03	1.066	.077	.198	7.05	AS3162-41	3.440	2.451	2.572	16.63
AS3162-04	1.128	.139	.260	7.30	AS3162-42	3.503	2.514	2.635	16.89
AS3162-05	1.190	.201	.322	7.54	AS3162-43	3.566	2.577	2.698	17.14
AS3162-06	1.253	.264	.385	7.80	AS3162-44	3.628	2.639	2.760	17.40
AS3162-07	1.316	.327	.448	8.05	AS3162-45	3.690	2.701	2.822	17.64
AS3162-08	1.378	.389	.510	8.31	AS3162-46	3.753	2.764	2.885	17.89
AS3162-09	1.440	.451	.572	8.55	AS3162-47	3.816	2.827	2.948	18.15
AS3162-10	1.503	.514	.635	8.81	AS3162-48	3.878	2.889	3.010	18.40
AS3162-11	1.566	.577	.698	9.06	AS3162-49	3.940	2.951	3.072	18.65
AS3162-12	1.628	.639	.760	9.32	AS3162-50	4.003	3.014	3.135	18.91
AS3162-13	1.690	.701	.822	9.56	AS3162-51	4.006	3.077	3.198	19.17
AS3162-14	1.753	.764	.885	9.82	AS3162-52	4.128	3.139	3.260	19.41
AS3162-15	1.816	.827	.948	10.08	AS3162-53	4.190	3.201	3.322	19.65
AS3162-16	1.878	.889	1.010	10.33	AS3162-54	4.253	3.264	3.385	19.92
AS3162-17	1.940	.951	1.072	10.58	AS3162-55	4.316	3.327	3.448	20.17
AS3162-18	2.003	1.014	1.135	10.84	AS3162-56	4.378	3.389	3.510	20.42
AS3162-19	2.066	1.077	1.198	11.09	AS3162-57	4.440	3.451	3.572	20.68
AS3162-20	2.128	1.139	1.260	11.33	AS3162-58	4.503	3.514	3.635	20.93
AS3162-21	2.190	1.201	1.322	11.59	AS3162-59	4.566	3.577	3.698	21.19
AS3162-22	2.253	1.264	1.385	11.84	AS3162-60	4.628	3.639	3.760	21.43
AS3162-23	2.316	1.327	1.448	12.10	AS3162-61	4.690	3.701	3.822	21.68
AS3162-24	2.378	1.389	1.510	12.34	AS3162-62	4.753	3.764	3.885	21.94
AS3162-25	2.440	1.451	1.572	12.60	AS3162-63	4.816	3.827	3.948	22.19
AS3162-26	2.503	1.514	1.635	12.85	AS3162-64	4.878	3.889	4.010	22.44
AS3162-27	2.566	1.577	1.698	13.11	AS3162-65	4.940	3.951	4.072	22.69
AS3162-28	2.628	1.639	1.760	13.36	AS3162-66	5.003	4.014	4.135	22.95
AS3162-29	2.690	1.701	1.822	13.61	AS3162-67	5.066	4.077	4.198	23.20
AS3162-30	2.753	1.764	1.885	13.86	AS3162-68	5.128	4.139	4.260	23.45
AS3162-31	2.816	1.827	1.948	14.12	AS3162-69	5.190	4.201	4.322	23.70
AS3162-32	2.878	1.889	2.010	14.36	AS3162-70	5.253	4.264	4.385	23.96
AS3162-33	2.940	1.951	2.072	14.61	AS3162-71	5.316	4.327	4.448	24.21
AS3162-34	3.003	2.014	2.135	14.87	AS3162-72	5.378	4.389	4.510	24.45
AS3162-35	3.066	2.077	2.198	15.12	AS3162-73	5.440	4.451	4.572	24.71
AS3162-36	3.128	2.139	2.260	15.38	AS3162-74	5.503	4.514	4.635	24.96
AS3162-37	3.190	2.201	2.322	15.62					
AS3162-38	3.253	2.264	2.385	15.88					
AS3162-39	3.316	2.327	2.448	16.13					
AS3162-40	3.378	2.389	2.510	16.39					



AEROSPACE STANDARD

(R) BOLT, MACHINE - DOUBLE HEXAGON EXTENDED
WASHER HEAD, DRILLED, CLOSE TOLERANCE
SHANK, AMS4967, .5625-18 UNJF-3A

AS3162
SHEET 2 OF 3

REV.
A