

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.



SAE Aerospace
An SAE International Group

REV.
B

REV.
B

AS3253

TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NO.	L	N MIN	M MAX	APPROX. MASS LB/100	PART NO.	L	N MIN	M MAX	APPROX. MASS LB/100
AS3253-03	.552 - .572	.025	.108	3.06	AS3253-32	2.740 - 2.760	1.607	1.750	9.26
AS3253-04	.615 - .635	.025	.108	3.24	AS3253-33	2.865 - 2.885	1.732	1.875	9.61
AS3253-05	.678 - .698	.025	.108	3.42	AS3253-34	2.990 - 3.010	1.857	2.000	9.97
AS3253-06	.740 - .760	.025	.108	3.59	AS3253-35	3.115 - 3.135	1.982	2.125	10.32
AS3253-07	.802 - .822	.025	.108	3.77	AS3253-36	3.240 - 3.260	2.107	2.250	10.67
AS3253-08	.865 - .885	.025	.108	3.94	AS3253-37	3.365 - 3.385	2.232	2.375	11.03
AS3253-09	.928 - .948	.025	.108	4.12	AS3253-38	3.490 - 3.510	2.357	2.500	11.39
AS3253-10	.990 - 1.010	.025	.108	4.30	AS3253-39	3.615 - 3.635	2.482	2.625	11.74
AS3253-11	1.052 - 1.072	.025	.108	4.47	AS3253-40	3.740 - 3.760	2.607	2.750	12.09
AS3253-12	1.115 - 1.135	.025	.125	4.65	AS3253-41	3.865 - 3.885	2.732	2.875	12.45
AS3253-13	1.178 - 1.198	.045	.188	4.83	AS3253-42	3.990 - 4.010	2.857	3.000	12.80
AS3253-14	1.240 - 1.260	.107	.250	5.00	AS3253-43	4.115 - 4.135	2.982	3.125	13.15
AS3253-15	1.302 - 1.322	.169	.312	5.19	AS3253-44	4.240 - 4.260	3.107	3.250	13.50
AS3253-16	1.365 - 1.385	.232	.375	5.37	AS3253-45	4.365 - 4.385	3.232	3.375	14.87
AS3253-17	1.428 - 1.448	.295	.438	5.54	AS3253-46	4.490 - 4.510	3.357	3.500	14.22
AS3253-18	1.490 - 1.510	.357	.500	5.72	AS3253-47	4.615 - 4.635	3.482	3.625	14.57
AS3253-19	1.552 - 1.572	.419	.562	5.90	AS3253-48	4.740 - 4.760	3.607	3.750	14.93
AS3253-20	1.615 - 1.635	.482	.625	6.07	AS3253-49	4.865 - 4.885	3.732	3.875	15.28
AS3253-21	1.678 - 1.698	.545	.688	6.25	AS3253-50	4.990 - 5.010	3.857	4.000	15.63
AS3253-22	1.740 - 1.760	.607	.750	6.43	AS3253-51	5.115 - 5.135	3.982	4.125	15.99
AS3253-23	1.802 - 1.822	.669	.812	6.60	AS3253-52	5.240 - 5.260	4.107	4.250	16.34
AS3253-24	1.865 - 1.885	.732	.875	6.78	AS3253-53	5.365 - 5.385	4.232	4.375	16.70
AS3253-25	1.928 - 1.948	.795	.938	6.96	AS3253-54	5.490 - 5.510	4.357	4.500	17.05
AS3253-26	1.990 - 2.010	.857	1.000	7.13	AS3253-55	5.615 - 5.635	4.482	4.625	17.39
AS3253-27	2.115 - 2.135	.982	1.125	7.48	AS3253-56	5.740 - 5.760	4.607	4.750	17.73
AS3253-28	2.240 - 2.260	1.107	1.250	7.84	AS3253-57	5.865 - 5.885	4.732	4.875	18.07
AS3253-29	2.365 - 2.385	1.232	1.375	8.20	AS3253-58	5.990 - 6.010	4.857	5.000	18.41
AS3253-30	2.490 - 2.510	1.357	1.500	8.55					
AS3253-31	2.615 - 2.635	1.482	1.625	8.91					