

REV.
A

SAE AS39029/37

FEDERAL SUPPLY CLASS
5999

RATIONALE

REVISE TO INCLUDE COMMENTS RECEIVED BY THE GOVERNMENT AND INDUSTRY SINCE 1988, INCORPORATES VARIOUS AMENDMENTS, REMOVE GOVERNMENT JARGON AS A RESULT OF THE WORD-FOR-WORD TRANSFERENCE OF AS39029 TO SAE, UPDATE SPECIFICATION REFERENCES, ALIGN SPECIFICATIONS WITH SAE GUIDELINES AS NEEDED, AND REVIEW SPECIFICATIONS FOR KNOWN TECHNICAL PROBLEMS.

NOTICE

THE REQUIREMENTS FOR PROCURING THE CONTACTS DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION AND THE LATEST ISSUE OF: SAE AS39029.





FIGURE 1- AS39029/37 SOCKET CONTACT

TABLE 1- CONTACT DIMENSIONS

BIN CODE	A DIA	B DIA	C DIA	D DIA
279	.048 .045	.070 .068	.079 .076	.119 .116
280	.070 .067	.090 .088	.112 .109	.119 .116

SAE values your input. To provide feedback on this Technical Report, please visit <http://www.sae.org/technical/standards/AS39029/37A>

THIRD ANGLE PROJECTION



CUSTODIAN: AE-8/AE-8C1

PROCUREMENT SPECIFICATION: AS39029

SAE Aerospace
An SAE International Group

AEROSPACE STANDARD

(R) CONTACTS, ELECTRICAL CONNECTOR, SOCKET, CRIMP REMOVABLE
(FOR MIL-DTL-28748/10 CONNECTORS)

SAE AS39029/37
SHEET 1 OF 3

REV.
A

TABLE 2- MARKING AND DESIGN CHARACTERISTICS

BIN CODE	COLOR BAND			MATING END SIZE	WIRE BARREL SIZE	TYPE	CLASS
	FIRST	SECOND	THIRD				
279	RED	VIOLET	WHITE	16	20	A	A
280	RED	GRAY	BLACK	16	16	A	A

TABLE 3- TOOL REQUIREMENTS

BIN CODE	BASIC CRIMPING TOOL	POSITIONER	INSTALLING TOOL	REMOVAL TOOL
279	M22520/1-01	M22520/1-03 BLUE	M81969/18-01	M81969/20-01
280	M22520/1-01	M22520/1-03 RED	M81969/18-01	M81969/20-01

TABLE 4- PART NUMBERS

AS39029 PART NUMBER	BIN CODE	SUPERSEDED PART NUMBER(S)
M39029/37-279	279	MS17808-16-20
M39029/37-280	280	MS17808-16-16

DETAIL SPECIFICATION REQUIREMENTS:

1. DESIGN:

CONTACT SHALL BE DESIGNED IN ACCORDANCE WITH FIGURE 1, TABLE 1 AND 2. WALL THICKNESS OF ANY PART OF THE CONTACT SHALL NOT BE LESS THAN 0.010 (0.25 MM) DIMENSIONS ARE IN INCHES AND SHOWN AFTER PLATING. UNLESS OTHERWISE SPECIFIED, SPHERICAL END DIMENSIONS SHALL CONFORM TO AS39029. ALL DIMENSIONS IN PARENTHESES ARE METRIC EQUIVALENTS AND PROVIDED FOR GENERAL INFORMATION ONLY (SEE AS39029 SECTION 6.0).

2. TOOLS:

TOOLS REQUIRED FOR CRIMPING CONTACTS TO WIRE/CABLE AND THE INSTALLING/REMOVAL FROM THE CONNECTOR SHALL BE IN ACCORDANCE WITH TABLE 3.

3. PART NUMBERS:

CONTACT PART NUMBERS SHALL BE IN ACCORDANCE WITH TABLE 4. SUPERSEDING PART NUMBERS ARE AS SPECIFIED.

4. MATERIALS:

MATERIALS SHALL BE IN ACCORDANCE WITH AS39029.

5. MECHANICAL:

MECHANICAL PROPERTIES SHALL BE IN ACCORDANCE WITH AS39029.

6. ELECTRICAL:

ELECTRICAL PROPERTIES SHALL BE IN ACCORDANCE WITH AS39029.

	AEROSPACE STANDARD	SAE AS39029/37 SHEET 2 OF 3	REV. A
	(R) CONTACTS, ELECTRICAL CONNECTOR, SOCKET, CRIMP REMOVABLE (FOR MIL-DTL-28748/10 CONNECTORS)		