

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

AS4582

FEDERAL SUPPLY CLASS
4720

RATIONALE

AS4582 HAS BEEN REAFFIRMED TO COMPLY WITH THE SAE FIVE-YEAR REVIEW POLICY.





FIGURE 1- HOSE ASSEMBLY, STRAIGHT TO 90° ELBOW

SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/AS4582>

THIRD ANGLE PROJECTION



CUSTODIAN: G-3/G-3D

PROCUREMENT SPECIFICATION: AS1975 /2/



AEROSPACE STANDARD

HOSE ASSEMBLY, PTFE, PARA-ARAMID REINFORCED,
STANDARD DUTY, 4000 PSI, 275 °F, TITANIUM
FITTINGS, FLARELESS, STRAIGHT TO 90°

AS4582
SHEET 1 OF 6

TABLE 1 - ASSEMBLY DIMENSIONS

HOSE ASSEMBLY NO. & SIZE CODE	HOSE SIZE (REF)	/15/ FITTING TYPE (REF)	THREAD T PER AS8879 (REF)	HOSE ID MIN	A ₁ MAX	A ₂ MAX	B GAGE BASIC	C /7/ MIN STR FTG BORE AFTER ASSEMBLY	D (REF)
AS4582E	.250	-							
AS4582E	.250	S	.4375-20UNJF-3B	.212	1.630	1.880	.2930	.135	.16
AS4582E	.250	E	.5625-18UNJF-3B	.212	1.695	1.930	.4120	.135	.16
AS4582G	.375	R	.4375-20UNJF-3B	.298	1.725	2.180	.2930	.135	.16
AS4582G	.375	S	.5625-18UNJF-3B	.298	1.835	2.180	.4120	.240	.16
AS4582G	.375	E	.7500-16UNJF-3B	.298	1.915	2.530	.5600	.240	.19
AS4582H	.500	R	.5625-18UNJF-3B	.391	2.145	2.530	.4120	.240	.16
AS4582H	.500	S	.7500-16UNJF-3B	.391	2.165	2.530	.5600	.340	.19
AS4582H	.500	E	.8750-14UNJF-3B	.391	2.675	2.780	.6730	.340	.20
AS4582J	.625	R	.7500-16UNJF-3B	.485	2.860	3.375	.5600	.340	.19
AS4582J	.625	S	.8750-14UNJF-3B	.485	2.905	3.375	.6730	.410	.20
AS4582J	.625	E	1.0625-12UNJ-3B	.485	2.920	3.655	.8100	.410	.23
AS4582K	.750	R	.8750-14UNJF-3B	.602	3.240	3.940	.6730	.410	.20
AS4582K	.750	S	1.0625-12UNJ-3B	.602	3.205	3.940	.8100	.510	.23
AS4582K	.750	E	1.3125-12UNJ-3B	.602	3.320	4.060	1.0620	.510	.30
AS4582M	1.000	R	1.0625-12UNJ-3B	.852	3.690	4.485	.8100	.510	.23
AS4582M	1.000	S	1.3125-12UNJ-3B	.852	3.740	4.485	1.0620	.760	.30
AS4582M	1.000	E	1.5625-12UNJ-3B	.852	3.570	4.680	1.3160	.760	.04
AS4582N	1.250	R	1.3125-12UNJ-3B	1.100	4.600	5.085	1.0620	.760	.30
AS4582N	1.250	S	1.5625-12UNJ-3B	1.100	4.330	5.225	1.3160	.960	.04
AS4582N	1.250	-	TBD	TBD	TBD	TBD	TBD	TBD	TBD
AS4582P	1.500	-							
AS4582P	1.500	S	TBD	TBD	TBD	TBD	TBD	TBD	TBD
AS4582P	1.500	-							



AEROSPACE STANDARD

HOSE ASSEMBLY, PTFE, PARA-ARAMID REINFORCED,
STANDARD DUTY, 4000 PSI, 275 °F, TITANIUM
FITTINGS, FLARELESS, STRAIGHT TO 90°

AS4582
SHEET 2 OF 6

TABLE 1 (CONTINUED)

HOSE ASSEMBLY NO. & SIZE CODE	HOSE SIZE (REF)	/15/ FITTING TYPE (REF)	E /8/ DIA MAX WITHOUT SLEEVING	F HEX (REF)	G MIN	G MAX	SPHERICAL BALL SIZE FOR DETERMINING MINIMUM HOSE ASSEMBLY ID /7/ IN STRAIGHT FITTING	SPHERICAL BALL SIZE FOR DETERMINING MINIMUM HOSE ASSEMBLY ID /7/ IN ELBOW FITTING
AS4582E	.250	-						
AS4582E	.250	S	.69	.56	.645	.770	.122	.115
AS4582E	.250	E	.69	.69	.715	.840	.122	.115
AS4582G	.375	R	.80	.56	.645	.770	.122	.115
AS4582G	.375	S	.80	.69	.715	.840	.216	.204
AS4582G	.375	E	.80	.88	.845	.970	.216	.204
AS4582H	.500	R	.97	.69	.715	.840	.216	.204
AS4582H	.500	S	.97	.88	.845	.970	.306	.289
AS4582H	.500	E	.97	1.00	1.085	1.210	.306	.289
AS4582J	.625	R	1.15	.88	.845	.970	.306	.289
AS4582J	.625	S	1.15	1.00	1.085	1.210	.369	.349
AS4582J	.625	E	1.15	1.25	1.275	1.400	.369	.349
AS4582K	.750	R	1.38	1.00	1.085	1.210	.369	.349
AS4582K	.750	S	1.38	1.25	1.275	1.400	.459	.434
AS4582K	.750	E	1.38	1.50	1.500	1.625	.459	.434
AS4582M	1.000	R	1.66	1.25	1.275	1.400	.459	.434
AS4582M	1.000	S	1.66	1.50	1.500	1.625	.684	.646
AS4582M	1.000	E	1.66	1.81	1.700	1.825	.684	.646
AS4582N	1.250	R	2.33	1.50	1.500	1.625	.684	.646
AS4582N	1.250	S	2.33	1.81	1.700	1.825	.864	.816
AS4582N	1.250		TBD	TBD	TBD	TBD	TBD	TBD
AS4582P	1.500	-						
AS4582P	1.500	S	TBD	TBD	TBD	TBD	TBD	TBD
AS4582P	1.500	-						

TABLE 2 - HOSE AND SLEEVE OUTSIDE DIAMETER

SLEEVE CODE	SLEEVE MATERIAL	TEMP LIMIT °F	TOLERANCE	HOSE SIZE /10/ .250	HOSE SIZE /10/ .375	HOSE SIZE /10/ .500	HOSE SIZE /10/ .625	HOSE SIZE /10/ .750	HOSE SIZE /10/ 1.000	HOSE SIZE /10/ 1.250	HOSE SIZE /10/ 1.500
-	BRAIDED HOSE ONLY PER AS1975	275	MAX MIN	.465 .405	.555 .495	.710 .650	.920 .850	1.075 .995	1.365 1.285	1.660 1.580	TBD TBD
A	FIRESLEEVE (AS1072 SIL FG) (5 min) /11/ /12/	275	MAX MIN	.840 .658	.970 .788	1.150 .968	1.380 1.198	1.590 1.318	1.750 1.568	1.950 1.768	TBD TBD
B	FIRESLEEVE INTEGRAL SILICONE (5 min) /13/	275	MAX MIN	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
C	PROTECTIVE SLEEVE SHRINK-ON (POLYOLEFIN AS1073 CODE B) /21/	275	MAX MIN	.520 .450	.620 .550	.795 .725	1.000 .920	1.170 1.060	1.460 1.350	TBD	TBD

TABLE 3 - ASSEMBLY LENGTH TOLERANCE

HOSE ASSEMBLY LENGTH	TOLERANCE
UNDER 18 in	±.125 in
18 THRU 36 in EXCLUSIVE	±.250 in
36 THRU 50 in EXCLUSIVE	±.500 in
50 in AND OVER	±1%

TABLE 4 - HOSE AND FITTING WEIGHTS

HOSE OR SLEEVE CODE	HOSE OR SLEEVE OR PART	UNITS	HOSE SIZE .250	HOSE SIZE .375	HOSE SIZE .500	HOSE SIZE .625	HOSE SIZE .750	HOSE SIZE 1.000	HOSE SIZE 1.250	HOSE SIZE 1.500
-	BRAIDED HOSE ONLY PER AS1975	LB/IN (MAX)	.006	.008	.012	.020	.025	.040	.050	TBD
A	FIRESLEEVE AS1072 (5 min PER AS1055) /16/	LB/IN								
B	FIRESLEEVE INTEGRAL WITH HOSE (5 min PER AS1055) /16/	LB/IN								
C	PROTECTIVE SLEEVE SHRINK-ON (POLYOLEFIN AS1073, CODE B) /21/	LB/IN	.001	.001	.001	.002	.002	.003	TBD	TBD
NONE	FIRESLEEVE CLAMP	LB/EA (REF)	.020	.020	.021	.021	.025	.025	.032	TBD
NONE	FITTING END (STRAIGHT) TITANIUM /15/ /17/	R LB/EA (REF) S LB/EA (REF) E LB/EA (REF)	- .048 .068	.077 .081 .115	.118 .135 .193	.210 .248 .296	.382 .431 .546	.730 .760 .890	TBD TBD -	- TBD /9/ -
NONE	FITTING END (90°) TITANIUM /15/ /17/	R LB/EA (REF) S LB/EA (REF) E LB/EA (REF)	- .077 .099	.110 .121 .154	.143 .176 .242	.275 .297 .410	.460 .560 .740	.810 .950 1.075	TBD TBD -	- TBD /9/ -

**AEROSPACE STANDARD**

HOSE ASSEMBLY, PTFE, PARA-ARAMID REINFORCED,
STANDARD DUTY, 4000 PSI, 275 °F, TITANIUM
FITTINGS, FLARELESS, STRAIGHT TO 90°

AS4582
SHEET 4 OF 6