

Connector Accessories, Electrical, Backshell, Non-environmental, Strain Relief, Straight, Category 4A
(For MIL-DTL-5015 Solder Type, V Thread of 310X, Classes A, B, C or K Connectors)

This amendment forms a part of AS85049/42A Dated 2006-06

1). Present Requirement: (Sheet 1)

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of SAE AS85049

Change Requirements: (sheet 1)

NOTICE

The requirements for procuring the product described herein shall consist of this specification sheet and the latest issue of SAE AS85049.

Rationale for Change: Up-dated the procurement statement to comply with SAE guidelines.

2). Present Requirement: (Table 2, Material and Finish, sheet 4)

TABLE 2 - MATERIAL AND FINISH

COMPONENT	MATERIAL	FINISH
BODY	ALUMINUM ALLOY IN ACCORDANCE WITH AS85049	1/ N, 2/ W
BODY	CORROSION RESISTANT STEEL IN ACCORDANCE WITH AS85049	B, S

1/ NOT FOR NAVY USE. RESTRICTED TO AIR FORCE SPACE APPLICATIONS ONLY.
2/ W FINISH IS NOT FOR USE IN SPACE APPLICATION.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2010 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE values your input. To provide feedback
on this Technical Report, please visit
http://www.sae.org/technical/standards/AS85049/42A_A1