

NEW PART STANDARD TO REPLACE MS9706.

NOTICE

THE INITIAL SAE PUBLICATION OF THIS DOCUMENT WAS TAKEN DIRECTLY FROM U.S. MILITARY STANDARD MS9706A. THIS SAE STANDARD MAY RETAIN THE SAME PART NUMBERS ESTABLISHED BY THE ORIGINAL MILITARY DOCUMENT.

ANY REQUIREMENTS ASSOCIATED WITH QUALIFIED PRODUCTS LISTS (QPL'S) MAY CONTINUE TO BE MANDATORY FOR DoD CONTRACTS. REQUIREMENTS RELATING TO QPL'S HAVE NOT BEEN ADOPTED BY THE SAE FOR THIS STANDARD AND ARE NOT PART OF THIS SAE DOCUMENT.

AS9706™

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions. SAE Executive Standards Committee provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."





FIGURE 1 - BOLT

For more information on this standard, visit
<https://www.sae.org/standards/content/AS9706>

THIRD ANGLE PROJECTION



CUSTODIAN: E-25

PROCUREMENT SPECIFICATION: AS7471



AEROSPACE STANDARD

SCREW, MACHINE - DOUBLE HEXAGON EXTENDED
WASHER HEAD, DRILLED, NICKEL ALLOY
(UNS N07001), .2500-28 UNJF-3A

AS9706™
SHEET 1 OF 3

TABLE 1 - PART NUMBERS AND DIMENSIONS

PART NUMBER	L	K	APPROX MASS LB/100	PART NUMBER	L	K	APPROX MASS LB/100
MS9706-04	.365- .385	.062- .082	1.06	MS9706-19	1.302-1.322	.674- .724	2.38
MS9706-05	.428- .448	.062- .082	1.33	MS9706-20	1.365-1.385	.737- .797	2.46
MS9706-06	.490- .510	.062- .082	1.41	MS9706-21	1.428-1.448	.800- .860	2.53
MS9706-07	.552- .572	.062- .082	1.48	MS9706-22	1.490-1.510	.862- .922	2.61
MS9706-08	.615- .635	.062- .082	1.56	MS9706-23	1.552-1.572	.924- .984	2.68
MS9706-09	.678- .698	.062- .110	1.63	MS9706-24	1.615-1.635	.987-1.047	2.76
MS9706-10	.740- .760	.112- .172	1.71	MS9706-25	1.678-1.698	1.050-1.110	2.88
MS9706-11	.802- .822	.174- .234	1.78	MS9706-26	1.740-1.760	1.112-1.172	2.91
MS9706-12	.865- .885	.237- .297	1.86	MS9706-27	1.802-1.822	1.174-1.234	2.98
MS9706-13	.928- .948	.300- .360	1.93	MS9706-28	1.865-1.885	1.237-1.297	3.06
MS9706-14	.990-1.010	.362- .422	2.01	MS9706-29	1.990-2.010	1.362-1.422	3.21
MS9706-15	1.052-1.072	.424- .484	2.08	MS9706-30	2.115-2.135	1.315-1.375	3.36
MS9706-16	1.115-1.135	.487- .547	2.16	MS9706-31	2.240-2.260	1.440-1.500	3.51
MS9706-17	1.178-1.198	.550- .610	2.23	MS9706-32	2.365-2.385	1.565-1.625	3.66
MS9706-18	1.240-1.260	.612- .672	2.31	MS9706-33	2.490-2.510	1.690-1.750	3.81
MS9706-34	2.615-2.635	1.815-1.875	3.96	MS9706-49	4.490-5.010	3.690-3.750	6.20
MS9706-35	2.740-2.760	1.940-2.000	4.11	MS9706-50	4.615-4.635	3.815-3.875	6.35
MS9706-36	2.865-2.885	2.065-2.125	4.26	MS9706-51	4.740-4.760	3.940-4.000	6.50
MS9706-37	2.990-3.010	2.190-2.250	4.41	MS9706-52	4.865-4.885	4.065-4.125	6.65
MS9706-38	3.115-3.135	2.315-2.375	4.56	MS9706-53	4.990-5.010	4.190-4.250	6.80
MS9706-39	3.240-3.260	2.440-2.500	4.71	MS9706-54	5.115-5.135	4.315-4.375	6.95
MS9706-40	3.365-3.385	2.565-2.625	4.86	MS9706-55	5.240-5.260	4.440-4.500	7.10
MS9706-41	3.490-3.510	2.690-2.750	5.00	MS9706-56	5.365-5.385	4.565-4.625	7.25
MS9706-42	3.615-3.635	2.815-2.875	5.15	MS9706-57	5.490-5.510	4.690-4.750	7.40
MS9706-43	3.740-3.760	2.940-3.000	5.30	MS9706-58	5.615-5.635	4.815-4.875	7.55
MS9706-44	3.865-3.885	3.065-3.125	5.45	MS9706-59	5.740-5.760	4.940-5.000	7.70
MS9706-45	3.990-4.010	3.190-3.250	5.60	MS9706-60	5.865-5.885	5.065-5.125	7.85
MS9706-46	4.115-4.135	3.315-3.375	5.75	MS9706-61	5.990-6.010	5.190-5.250	8.00
MS9706-47	4.240-4.260	3.440-3.500	5.90				
MS9706-48	4.365-4.385	3.565-3.625	6.05				

NOTES:

- /1/ FOR PARTS NUMBERS MS9706-04 THRU MS9706-14, DATUM Z SHALL REPLACE DATUM Y.
2. MATERIAL: AMS5708 (COMPOSITION SIMILAR TO UNS N07001).
- /3/ PROCUREMENT SPECIFICATION: AS7471.
4. HEAD TO SHANK FILLET SHOULD NOT BE COLD ROLLED FOR DASH NUMBERS -14 AND SMALLER
5. FLUORESCENT PENETRANT INSPECT PER ASTM E1417/E1417M, TYPE 1, SENSITIVITY LEVEL 2.
6. SURFACE TEXTURE: SYMBOLS PER ASME Y14.36M. REQUIREMENTS PER ASME B46.1. UNLESS OTHERWISE SPECIFIED, SURFACES TO BE 125 MICROINCHES Ra.
7. BREAK SHARP EDGES .003 TO .015, UNLESS OTHERWISE SPECIFIED.
8. DIMENSIONS ARE IN INCHES.
9. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1983.
10. DO NOT USE UNASSIGNED PART NUMBERS.

	AEROSPACE STANDARD	AS9706™ SHEET 2 OF 3	
	SCREW, MACHINE - DOUBLE HEXAGON EXTENDED WASHER HEAD, DRILLED, NICKEL ALLOY (UNS N07001) 2500-28 UNJF-3A		