



SURFACE VEHICLE STANDARD



J1472 DEC2013

Issued 1987-06
Cancelled 2013-12

Superseding J1472 SEP2006

Braking Performance - Rollers

RATIONALE

ISO 3450 was revised to include the rollers in the last revision. Therefore, all the requirements of J1472 are covered in ISO 3450. SAE J1472 is superseded by ISO 3450.

SAENORM.COM : Click to view the full PDF of j1472_201312

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2013 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

**SAE values your input. To provide feedback
on this Technical Report, please visit
http://www.sae.org/technical/standards/J1472_201312**

SAE WEB ADDRESS:

At the five-year review, a need was recognized to update SAE J1472. Revisions have been made to clarify the use of hydrostatic drives as a service brake system. Other changes and additions have been made to make it consistent with other current and recently revised SAE braking documents.

1. SCOPE

This SAE Standard specifies brake system performance and test criteria to enable uniform evaluation of the braking capability of self-propelled, ride-on vibratory steel wheel, static steel wheel, and rubber-tire rollers with maximum level surface machine speeds of 25 km/h or less. Service, secondary, and parking brakes are included. Machines with maximum level surface machine speeds greater than 25 km/h shall conform to the requirements of ISO 3450.

1.1 Application

This document applies to self-propelled, ride-on vibratory steel wheel, static steel wheel, and rubber-tire rollers as defined in ISO 6165 and ISO 8811 and as listed in SAE J1116, and to these same machines while in service.

2. REFERENCES

2.1 Applicable Publications

The following publications form a part of this specification to the extent specified herein. Unless otherwise indicated the latest revision of SAE and ISO publications shall apply.

2.1.1 SAE Publication

Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), www.sae.org.

SAE J1116 Categories of Off-Road Self-Propelled Work Machines

SAENORM.COM : Click to view the full PDF of J1472-2013

2.1.2 ISO Publications

Available from ANSI, 25 West 43rd Street, New York, NY 10036-8002, Tel: 212-642-4900, www.ansi.org.

ISO 6165 Earthmoving machinery—Basic types—Vocabulary

ISO 8811 Earthmoving machinery—Rollers and compactors—Terminology and commercial specifications

ISO 9248 Earthmoving machinery—Units for dimensions, performance, and capacities and their measurement accuracies

3. DEFINITIONS

3.1 Brake Systems

All the components which combine together to stop and/or hold the machine. Such systems consist of the control(s), means of brake actuation, the brake(s), and all parts connecting the brake(s) to the steel wheels or tires.

3.1.1 Service Brake System

The primary system used for stopping and holding the machine.

3.1.2 Secondary Brake System

The system used for stopping the machine in the event of any single failure in the service brake system.

3.1.3 Parking Brake System

The system used to hold a stopped machine in a stationary position.

3.2 Brake System Components

3.2.1 Control

Component directly activated by the operator to cause a force to be transmitted to the brake(s).

3.2.2 Brake Actuation System

All the components between the control(s) and the brake(s) which connect them functionally.

3.2.3 Brake

Component, which directly applies a force to oppose movement of the machine. Brakes, for example, may be friction, electrical, hydrostatic or other fluid types.

3.3 Common Component

A component that performs a function in two or more brake systems.

3.4 Back Throttling

The action of applying slight forward or reverse power to a hydrostatic machine to hold the machine stationary on a slope.

3.5 Stopping Distance

Distance traveled by the machine from the point on the test course at which the brake control actuation begins to the point on the test course where the machine is fully stopped.

3.6 Machine Mass

The manufacturer's stated maximum machine mass with an operator of 75 kg, with the machine fully fueled and serviced, and with the sprinkler water reservoir(s) full.

4. GENERAL BRAKE SYSTEM REQUIREMENTS

4.1 Required Brake Systems

Machines shall be equipped with:

- a. A Service Brake System
- b. A Secondary Brake System
- c. A Parking Brake System

4.2 No brake system shall contain a disconnect such as a clutch or shiftable gearbox which allows disabling the brake(s) with the exception of 4.2.1 and 4.2.2 below.

- 4.2.1 A brake disconnect designed to allow movement of a disabled machine shall be able to be reapplied immediately or it must be in a location from which it can be operated from ground level.
- 4.2.2 A power-source disconnect designed for cold-weather starting which also disables the service or secondary brake system, shall require application of the parking brake prior to disconnection.

4.3 Service Brake System

All machines shall meet the service brake performance requirements specified in 6.4.1 and 6.5.1.

4.3.1 If other systems are provided with power from the service brake system, any failure in these systems shall be considered the same as a failure in the service brake system.

4.4 Secondary Brake System

All machines shall meet the secondary brake performance requirements specified in 6.5.2.

4.5 Parking Brake System

All machines shall meet the parking brake performance requirements of 6.4.2.

4.5.1 After being applied, this system shall maintain the required parking performance despite any contraction of the brake parts or leakage of any kind. This system shall not be dependent upon an exhaustible energy source.

4.5.2 If the parking brake system is used as the secondary brake system, then the parking brake shall have dynamic stopping capability as defined in 6.5.2.

4.6 The previous systems may use common components. However, a failure of any single component shall not reduce the effectiveness of the machine's stopping capability to less than the secondary stopping performance, as defined in 6.5.2.

4.7 Brake System Controls

All brake system controls shall be capable of being applied from the operator's station. The secondary and parking system(s) control(s) shall be arranged so that they cannot be released from the operator's station after any application unless immediate reapplication can be made from the operator's station.

4.7.1 The secondary and parking brake systems may be applied automatically.

4.8 Warning Device (Stored Energy Sources)

If stored energy is used for the service brake system, that system shall be equipped with a warning device which activates before system energy drops below the greater of 50% of the manufacturer's specified maximum operating energy level or the level required to meet the secondary stopping requirements. The device shall readily attract the operator's attention by providing a continuing visual or audible warning. Gauges indicating pressure or vacuum do not meet this requirement.

5. BRAKE TEST CRITERION

5.1 Facilities and Instrumentation

5.1.1 The test course shall consist of a hard, dry surface (ground moisture may be present to the extent that it does not adversely affect the braking surface) with a well compacted base. The approach will be of sufficient length, smoothness, and uniformity of grade to assure stabilized travel speed of the machine. The test course shall not have more than 3% grade at right angles to the direction of travel. Grade in the direction of travel shall be as specified for the test being conducted.

5.1.2 Instrumentation shall be provided to measure and record the test parameters within the accuracy specified in ISO 9248.

5.2 Test Requirements

5.2.1 Manufacturer's precautions shall be observed while conducting performance tests.

5.2.2 All parameters related to brake systems shall be within the machine manufacturer's specifications; that is, tire size and pressure, brake adjustment, warning device actuation point, etc. All power-assist pressures shall be within the machine manufacturer's specification range. No manual adjustment(s) shall be made to the brake system during any one performance test.

5.2.2.1 Burnishing (conditioning) of brakes before testing is permissible. The burnishing procedure shall be indicated in the operator's and/or maintenance manual for the machine and shall be verified by consultation with the machine manufacturer.

5.2.3 Machine Mass

The machine is to be tested at the machine mass defined in 3.7.

5.2.4 Stopping distance is to be measured in meters from the point at which the brake control application begins to the point at which the machine is at rest.

5.2.5 Stopping performance tests are to be conducted from the maximum level surface machine speed per the machine manufacturer's specifications.

5.2.6 When the machine transmission provides a selection of speed ratios, the stopping tests shall be conducted with the transmission in the speed ratio corresponding to the test speed specified in 5.2.5. The powertrain may be disengaged prior to completing the stop.

5.2.7 Immediately prior to a test, the machine shall be operated until the engine, transmission, and machine fluids are at normal operating temperature.

5.2.8 On machines where hydrostatic braking is used as the service brake, the stopping and holding performance of this system shall be conducted with the engine running.

5.2.9 When testing a vibratory machine, all tests shall be conducted without vibration.

6. PERFORMANCE TESTS

6.1 Control Forces

Control forces needed by the operator to meet the required braking performance for the systems defined in Section 5 shall not exceed the values in Table 1.

TABLE 1 - MAXIMUM CONTROL FORCES FOR BRAKE TESTS

Control Type	Maximum Force Applied N
Finger Grasp (flip levers and switches)	20
Hand Grasp	
Upwards	400
Downwards	300
Fore-Aft	300
Sideways	300
Foot Pedal (leg control)	600
Foot Treadle (ankle control)	350

6.2 System Recovery (if applicable)

With the machine stationary, the service brake system's primary power source shall have capability of delivering at least 70% of maximum brake pressure measured at the brakes when brakes are fully applied 20 times at the rate of 6 applications per minute with the engine at maximum governed RPM.

6.3 Warning Device (Stored Energy System)

The service brake system energy shall be reduced by any suitable means. The warning device (see 4.8) shall activate before system energy drops below the greater of 50% of the manufacturer's specified maximum operating energy level or the stored energy level required to meet the secondary stopping requirements (see 6.5.2). The warning device shall activate prior to any automatic application of a secondary brake system.

6.4 Holding Performance

All machines shall be tested in both the forward and reverse directions on a test course as described in 5.1.1 with grade as specified as follows:

6.4.1 The service brake system shall be capable of holding the machine on a 20% grade. For machines using hydrostatic drives, back throttling may be used to meet this requirement.

6.4.2 The parking brake system shall be capable of holding the machine on a 20% grade. The drivetrain(s) shall be disengaged.

6.4.3 If the tests in 6.4.1 and 6.4.2 are impractical, the tests may be carried out either:

- a. On a tilt platform (a skid-resistant surface that may be inclined), or
- b. By applying a pulling force to the machine with the transmission in neutral on a test course as described in 5.1.1 with no more than 1% grade in the direction of travel. The pulling force shall be applied horizontally near the ground to achieve a minimum force equivalent to the grades specified in 6.4.1 and 6.4.2. The equivalent force in Newtons is obtained from the equation, $F = 9.8 \times \text{Mass} \times \sin \alpha$, where α is the grade in degrees and Mass is in kilograms. The equivalent force is 1.92 times machine mass for a 20% grade.